DATE: 5/15/06 PAGE 1 OF 7

### MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1. THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

PRODUCT IDENTITY:	STRIPPER
COMPANY IDENTITY:	TESCO PRODUCTS, INC.
COMPANY ADDRESS:	25601 Avenue Stanford
COMPANY CITY:	Valencia, CA 91355
COMPANY PHONE:	1-661-257-0153
Chem-Tel PHONE:	1-800-255-3924

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CONTAINS: 60-70% TOLUENE (108-88-3)[203-625-9], 30-35% 1-METHOXY-2-PROPANOL (107-98-2) Number in parentheses is CAS #, number in brackets is European EC #.

SECTION 3. HAZARDS IDENTIFICATION

#### RISK STATEMENTS:

R11	Highly Flammable.
R36/37/38	Irritating to eyes, respiratory system and skin.
R20/65	Harmful by inhalation, may cause lung damage if swallowed.

### SAFETY STATEMENTS:

S16	Keep away from sources of ignition. No smoking.
S29	Do not empty into drains.
S24/25	Avoid contact with skin and eyes.

SECTION 4. FIRST AID MEASURES

# EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

#### SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

# INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

# SWALLOWING:

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting. Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal.

DATE: 5/15/06 PAGE 2 OF 7

#### SECTION 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA NFPA Class B extinguishers(Carbon Dioxide or foam)for Class I B liquid fires.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE Keep container tightly closed. Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

CONTAINMENT TECHNIQUES Stop spill at source. Dike area & contain.

CLEAN-UP PROCEDURES:

Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

SECTION 7. HANDLING AND STORAGE

#### HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

STORAGE

Do not store above 49 C/120 F. Store large amounts in structures made for OSHA Class I B liquids Keep container tightly closed & upright when not in use to prevent leakage.

DATE: 5/15/06 PAGE 3 OF 7

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION: EXPOSURE CONTROLS Use vapor, mist gas mask within use limits, or ventilate to keep vapors of this material below 30 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment. VENTILATION LOCAL EXHAUST : Necessary MECHANICAL (GENERAL) : Acceptable SPECIAL : None OTHER : None PERSONAL PROTECTIONS: Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. WORK & HYGIENIC PRACTICES: Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing. SECTION 9. PHYSICAL DATA Liquid, Water-White APPEARANCE : Chlorine ODOR : 110 112 123 C / 231 235 254 F BOILING RANGE : AUTO IGNITION TEMPERATURE : 426 C / 800 F (Lowest Component) LOWER FLAMMABLE LIMIT IN AIR (% by vol): 1.6 FLASH POINT (TEST METHOD): 7 C / 45 F (TCC) (Lowest Component) FLAMMABILITY CLASSIFICATION: Class I B GRAVITY @ 60 F : 27.9 API : SPECIFIC GRAVITY (Water=1) : .888 POUNDS/GALLON : 7.396 

 VOC'S (>0.44 Lbs/Sq In):
 65.7 Vol. % / 583.6 g/L / 4.861 Lbs/Gal

 TOTAL VOC'S (TVOC):
 100.0 Vol. % / 887.8 g/L / 7.395 Lbs/Gal

TOTAL VOC'S (TVOC) : NONEXEMPT VOC'S (CVOC) : 100.0 Vol. % / 887.8 g/L / 7.395 Lbs/Gal HAZARDOUS AIR POLLUTANTS (HAPS) : 65.7 Wt. % / 582.9 g/L / 4.855 Lbs/Gal 17.8 VAPOR PRESSURE (mm of Hg)@20 C NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) 17.8 VAPOR DENSITY (air=1) : 3.1 WATER ABSORPTION : Appreciable **REFRACTIVE INDEX :** 1.465 MIXED ANILINE POINT (Acid Insol): 8 C / 47 F

DATE: 5/15/06 PAGE 4 OF 7

SECTION 10. STABILITY & REACTIVITY

STABILITY Stable

CONDITIONS TO AVOID Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

Isolate from strong oxidizers such as permanganates, chromates & peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

CAS # MATERIAL TWA (OSHA) TLV (ACGIH) HAP Toluene 108-88-3 200 ppm 50 ppm A4 Yes 1-Methoxy-2-propanol 107-98-2 None Known 100 ppm No In addition to EPA Hazardous Air Pollutants showing `Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Mixed Xylenes, Ethylbenzene

MATERIAL	CAS #	CEILING	STEL (OSHA/ACGIH)
1-Methoxy-2-propanol	107-98-2	None Known	150 ppm

#### ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis. Absorption thru skin increases exposure. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

SWALLOWING:

Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

DATE: 5/15/06 PAGE 5 OF 7

## SUBCHRONIC HAZARDS/CONDITIONS AGGREVATED

CONDITIONS AGGREVATED

Chronic overexposure can cause damage to kidneys, blood, nerves, liver & lungs. Persons with severe skin, liver or kidney problems should avoid use.

## CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS: Leukemia been reported in humans from Benzene. This product contains less than 196 ppm of Benzene. Not considered hazardous in such low concentrations. Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

SECTION 12. ECOLOGICAL INFORMATION

MAMMALIAN IN	IFORMATION:	
MATERIAL	CAS #	LOWEST KNOWN LETHAL DOSE DATA
		LOWEST KNOWN LD50 (ORAL)
Toluene	108-88-3	3000.0 mg/kg(Rats)
		LOWEST KNOWN LC50 (VAPORS)
Toluene	108-88-3	5300 ppm (Mice)
		LOWEST KNOWN LD50 (SKIN)
Toluene	108-88-3	4000.0 mg/kg (Rabbits)

### AQUATIC ANIMAL INFORMATION:

The most sensitive known aquatic group to any component of this product is: Juvenile Rainbow Trout are adversely affected by components of this product.

# MOBILITY

This material is a mobile liquid.

### DEGRADABILITY

This product is partially biodegradable.

#### ACCUMULATION

This product does not accumulate or biomagnify in the environment.

DATE: 5/15/06 PAGE 6 OF 7

#### SECTION 13. DISPOSAL CONSIDERATIONS

Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If questions exist, contact the appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

DOT SHIPPING NAME:Paint Related Material,3,UN1263,PG-IIDRUM LABEL:(FLAMMABLE LIQUID)IATA / ICAO:Paint Related Material,3,UN1263,PG-IIIMO / IMDG:Paint Related Material,3,UN1263,PG-IIEMERGENCY RESPONSEGUIDEBOOK NUMBER:127

SECTION 15. REGULATORY INFORMATION

EPA REGULATION: SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list. SARA Title III Section 313 Supplier Notification This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS# W	T. %	(REG. SECTION) RQ(	LBS)
*Toluene	108-88-3	65	(311,312,313,RCRA)	1000
1-Methoxy-2-propanol	107-98-2	34	(311,312)	None

IF > 1523 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" OF TOLUENE IS EXCEEDED.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: This product contains the following chemical known to the State of California to cause reproductive toxicity: Toluene.

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries: Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

DATE: 5/15/06 PAGE 7 OF 7

SECTION 16. OTHER INFORMATION

HAZARD RATINGS: HEALTH (NFPA): 1 HEALTH (HMIS): 2 FLAMMABILITY: 3 REACTIVITY: 0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

## EMPLOYEE TRAINING

Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

#### NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications.

All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.